

SPG Plastics Group  
Tape Product Line  
01/01/03

**Carton Sealing Tape**

Description	Backing (carrier)	Adhesive Type	Total Thickness (mils)	Application Temp. (°F)	Adhesion (oz./inch)	Tensile Strength (lbs./inch)	Elongation (% at break)	Applications
<b>CS17</b> Utility Grade - An economy polypropylene film coated with a water based acrylic.	BOPP	Acrylic	1.7	35 to 140	18	20	140	For economy carton sealing with hand dispensers. Used for light weight packaging.
<b>CS18A</b> Production Grade - A polypropylene film coated with a water based adhesive.	BOPP	Acrylic	1.8	35 to 140	20	20	140	For economy carton sealing, hand and machine grade. Used for light weight packaging.
<b>CS20A</b> Extra Production Grade - A polypropylene film coated with a water based acrylic.	BOPP	Acrylic	2.0	35 to 150	26	25	120	For general purpose carton sealing. 48mm for individual shipment up to 35 lbs. 72mm up to 55 lbs. Tan, Clear.
<b>CS20C</b> Extra Production Grade - Colors a polypropylene film coated with a water based acrylic adhesive.	BOPP	Acrylic	2.0	35 to 150	26	25	120	Used for color coding and identifications. Same application as CS20A. Colors: red, orange, yellow, green blue, white and black.
<b>CS22A</b> Extra Production Grade - A polypropylene film coated with a acrylic adhesive.	BOPP	Acrylic	2.2	32 to 150	23	20	140	Used for general purpose carton sealing with hand and machining applications. Tan, Clear.
<b>CS26A</b> Heavy Duty Carton Sealing A heavy gauge biaxially oriented polypropylene film, coated with acrylic adhesive. All temperature.	BOPP	Acrylic	2.6	35 to 150	25	28	150	Heavy duty carton sealing applications. Cold room applications, meat and poultry packers, dairy plants and frozen food processors. Tan and Clear.
<b>CS30A</b> Extra Heavy Duty Carton Sealing - Based on an extremely rugged film, coated with a high grade blend adhesive system. Excellent "wet out" or quick stick to fiberboard.	BOPP	Acrylic	3.0	35 to 150	32	44	160	High impact, tear and burst strength combined with outstanding properties of adhesive make this product on an outstanding choice for a wide range of packaging applications. Tan and Clear.
<b>CS36A</b> X-Extra Heavy Duty Carton Sealing - Based on an extremely rugged film, coated with a high grade blend adhesive system. Excellent "wet out" or quick stick to fiberboard.	BOPP	Acrylic	3.6	32 to 150	42	44	180	Extra high impact, tear and burst strength combined with outstanding properties of adhesive make this product on an outstanding choice for a wide range of packaging applications. Tan and Clear.